



Kikko Max is the new free standing vending machine with a 620 cup capacity and up to 7 canisters which complements the Necta Hot & Cold range. With a height of 1830 mm, it has been designed to stand alongside the similarly sized Snakky Max or Sfera machines. The Kikko Max works in a master/salve mode and utilizes a single payment system which provides "One-Stop-Shopping" and creates an appealing machine bank, ensuring the most user friendly and practical vending service available.

## **ELECTRONIC CONTROL**

The 16-bit electronic control with incorporated flash EPROM is extremely flexible and complete, as well as being compatible with the PC application "Flash". This allows a palmtop to be connected, via an RS232 interface, to allow the automatic set-up of the machine as well as the downloading of sales statistics and data (also in EVA-DTS format). With Flash it is also possible to have remote monitoring of the machine using GSM technology.

## **PAYMENT SYSTEMS**

Kikko Max is pre-set for the installation of systems with Executive, BDV and MDB protocol as well as for installation of validators.

- At the same time, the following can be fitted:
- Change-giver, validator or coin mechanismBill acceptor
- Cashless system with key or card.

## **ACCESSORIES**

Mechanical selections counter kit Lid for coin box kit Cup sensor + cup station lamp kit Cup station lamp kit 20 litre water tank kit 2x20 litre water tanks kit Still cooling unit kit (for powders) Master/slave kit RS232 jack kit GSM kit

POWER CONSUMPTION			
Espresso version To reach operating temperature For each hour of stand-by	51.71 Wh 100 Wh		
Instant version  To reach operating temperature For each hour of stand-by	174.1 Wh 88.7 Wh		

CAPACITY	
Cups (Ø 70-71 mm)	620*
Stirrers (length 95/105 mm)	550
Containers	6
Espresso boiler	0.6 I
Instant boiler	2
Coffee beans	3.2 kg
Instant coffee	0.9 kg
Chocolate	5.2 kg
Milk	2.6 kg
Tea	3.2 kg
Sugar	4 kg
*166 cc	

Optimum	internal	acces	s
Z 3000 pa	atented of	coffee	arour

CHARACTERISTICS		
Height	1830 mm*	
Width	540 mm	
Depth	650 mm	
Overall depth with door open	1120 mm	
Weight	126 kg ca.	
Power supply voltage	230 V	
Power supply frequency	50 Hz	
Installed power	1800 W	
Water mains pressure (With 3/4" gas male connection)	0.5 to 8.5 bar	
*Adjustable feet: +10 -10 mm		



**EXAMPLES OF POSSIBLE CONFIGURATIONS** 

(Ecorocco I Init

KIKKO MAX ES 6 KIKKO MAX IN 6

(6 conjeters)

	(Espresso Unit + 5 canisters)	(6 canisters)
Pre-selections		
Sugar dosing	■:	■:
Bean coffee black	₽	
Bean coffee long		
Bean café au lait	■:	
Bean coffee white	■:	
Instant espresso coffee		<u></u>
Coffee long		<u>=</u>
Café au lait		<u>=</u>
Coffee white		<u>=</u>
Cappuccino	<u>=</u> :	<b>_</b>
Chocolate	₽	<u></u>
Chocolate strong	<u></u>	<u></u>
Chocomilk	<u>=</u> :	<u>=</u>
Decaf/Instant coffee black	<u>=</u> :	<u>=</u>
Decaf/Instant coffee long	■:	<b>_</b>
Decaf/Instant café au lait	<u></u>	<b>_</b>
Decaf/Instant cappuccino	<u></u>	<u>=</u>
Lemon tea	<u>=</u> :	<u></u>
Soup		<u> </u>



Milk/Hot water
Cup only

No cup



3







N&W GLOBAL VENDING S.p.A.

Via Roma, 24 24030 Valbrembo (BG) Italy Tel. +39 035 606111 - Fax +39 035 606519